

LIST OF FIGURES

Fig.(1.1)	Basic growth processes (a) islands (b) layer by layer and (c) stransk-krastanov type	10
Fig.(1.2)	The four process of formation of thin film ..	14
Fig.(1.3)	Complex impedance Plot Z for the parallel circuit Rc.....	34
Fig.(1.4)	Complex imedpance plot Z for some simple circuits RC of different combinations	37
Fig.(2.1)	Shcematic diagram of coating unit (HBA 120/2).	48
Fig.(2.2)	The optical arrangement for producting multiple-beam fizea friuges at reflection ...	50
Fig.(2.3a)	PbTe thin film prepared for thickness measurements	52
Fig.(2.3b)	Interference pattern	52
Fig.(2.4)	The circuit used for the electrical D.C. measurments	54
Fig.(2.5)	The sample holder used for the electrical measurments	55
Fig.(2.6)	Impedance meter BM 507	57
Fig.(3.1A)	PbTe crystal structure	63
Fig.(3.1B)	Clsloed-back crystal structure of PbTe	63
Fig.(3.2)	Broadening of X-ray reflections due to small particle size	66
Fig.(3.3)	Effect of fine partical size on diffraction curves	69
Fig.(3.4)	X-ray diffractogram of PbTe powder.....	70
Fig.(3.5)	X-ray diffractogram of A freshly deposited PbTe film of different thicknesses	72
Fig.(3.6)	X-ray differectgram of PbTe films at 300°K and 573°K	75
Fig.(4.1)	Resistivity versus thickness for annealed PbTe films at 473°K, 573°K, 673°K for 30 min and 473°K for one hour	79

Fig.(4.2)	Resistivity times thickness versus thickness for annealed PbTe films at 473°K, 573°K, 673°K for 30 min	82
Fig.(4.3)	Resistivity times thickness versus thickness for annealed PbTe films at 473°K for one hour	83
Fig.(4.4)	A plot the log R of resistance versus reciprocal temperature for PbTe thin film (thicknesses 700, 550 nm)	88
Fig.(4.5)	Plots of log of resistance versus the reciprocal temperature for PbTe thin film of different thicknesses (700 to 50 nm).....	89
Fig.(4.6)	Complex impedance plot for RC parallel circuit and R_1C in series with R_2	93
Fig.(4.7a)	Z'' (Z') dependences for pbTe films at different thickness, at room temperature	98
Fig.(4.7b)	Z'' (Z') dependences for pbTe films at different thickness, at room temperature	99
Fig.(4.8a)	Dependence of (Z') on frequency of pbTe thin films of different thickness, at room temperature ..	100
Fig.(4.8b)	Dependence of (Z') on frequency of pbTe thin films of different thickness at room temperature	101
Fig.(4.9)	Z'' (Z') dependance of pbTe films at 323, 358, 373°K	102
Fig.(4.9)	Z'' (Z') dependance of pbTe films heated at 323°K, 358°K, 373°K	103
Fig.(4.10)	Van Itterback model	104
Fig.(4.11)	A plot of Z' VS f.at temperatures (323, 358, 373, 423, 463°K).....	105